

Manual Swinging Arm Type Fire Hose Reel

Model no.: FRNHR-01M



SPECIFICATIONS

Standard	BS EN 671
Type	Manual swinging arm
Hose ID	25mm
Hose Length & Type	30m, PVC lining and cover, twisted with polyster yarn
Disc & Drum	550mm disc, 180mm drum
Assembly Components	RAL3000 Reel, Red Hose, 1" Rotay Nozzle, 1" Angle Valve
Working Pressure	12bar
Testing Pressure	18bar
Nozzle Orifice Diameter	8mm
Flow Rate	39L/min at 2bar; 56L/min at 4bar; 68L/min at 6bar

FIRE PROTECTION SERVICES GLOBALLY

WE DELIVER ON OUR PROMISES

UK Office: 85 Great Portland street, First floor, London, W1W7LT, United Kingdom,
Tel:00442039210937, Tel +447708 000050

Automatic Swinging Arm Type Fire Hose Reel

Model no.: FRNHR-02A



SPECIFICATIONS

Standard	BS EN 671
Type	Automatic swinging arm
Hose ID	25mm
Hose Length & Type	30m, PVC lining and cover, twisted with polyster yarn
Disc & Drum	550mm disc, 180mm drum
Assembly Components	RAL3000 Reel, Red Hose, 1" Rotay Nozzle, 1" Angle Valve
Working Pressure	12bar
Testing Pressure	18bar
Nozzle Orifice Diameter	8mm
Flow Rate	39L/min at 2bar; 56L/min at 4bar; 68L/min at 6bar

FIRE PROTECTION SERVICES GLOBALLY

WE DELIVER ON OUR PROMISES

UK Office: 85 Great Portland street, First floor, London, W1W7LT, United Kingdom,
Tel:00442039210937, Tel +447708 000050